



# Tire Chart

## Skyjacker Suggested Tire/Wheel Specifications

Year	Vehicle Model	Max Tire Lift	Max Tire Height	Max Tire Width	Wheel Diameter	Wheel Width	Wheel Offset
<b>Chevrolet/GMC</b>							
99-03	Full Size IFS 4WD	6"	35"	12.5"	16"	8"	4.625"
88-98	Full Size IFS 4WD	2.5"	285	75	15-16"	8-9"	4.5"
88-98	Full Size IFS 4WD	6"	35"	12.5"	15-16"	8-9"	4.5"
88-91	Blazer, Jimmy, Sub	2.5"	33"	12.5"	15-16"	8-9"	3.5"- 4"
88-91	Blazer, Jimmy, Sub	4"	35"	12.5"	15-16"	8-9"	3.5"- 4"
88-91	Blazer, Jimmy, Sub	6"	37"	12.5"	15-16"	8-9"	3.5"- 4"
88-91	Blazer, Jimmy, Sub	8"	39"	12.5"	15-16"	10"	3.5"- 4"
73-87	Full Size 4WD	2.5"	33"	12.5"	15-16"	10"	3.5"- 4"
73-87	Full Size 4WD	4"	35"	12.5"	15-16"	10"	3.5"- 4"
73-87	Full Size 4WD	6"	37"	12.5"	15-16"	10"	3.5"- 4"
73-87	Full Size 4WD	8"	39"	12.5"	15-16"	10"	3.5"- 4"
67-72	Full Size 4WD	2.5"	34"	12.5"	15-16"	10"	3.5"- 4"
67-72	Full Size 4WD	4"	36"	12.5"	15-16"	10"	3.5"- 4"
67-72	Full Size 4WD	6"	38"	12.5"	15-16"	10"	3.5"- 4"
67-72	Full Size 4WD	8"	40"	12.5"	15-16"	10"	3.5"- 4"
<b>Hummer</b>							
03	H2	6"	39"	12.5"	17"	9"	4.625"
<b>Dodge</b>							
3-Feb	Ram Pickup 4WD	6"	37"	12.5"	17"	9"	5"
94-01	Ram Pickup 4WD	2-3"	33"	12.5"	15-16"	10"	4.625"
94-01	Ram Pickup 4WD	4-5"	35"	12.5"	15-16"	10"	4.625"
94-01	Ram Pickup 4WD	7"	38"	12.5"	15-16"	10"	4.625"
61-93	Full Size 4WD	2"	33"	12.5"	15-16"	10"	4"
61-93	Full Size 4WD	4"	35"	12.5"	15-16"	10"	4"
61-93	Full Size 4WD	6"	37"	12.5"	15-16"	10"	4"
61-93	Full Size 4WD	8"	39"	12.5"	15-16"	10"	4"
<b>Ford Ranger/Bronco II/Explorer</b>							
93-97	Ranger 4WD	2"	32"	12.5"	15"	8"	4"
93-97	Ranger 4WD	4"	33"	12.5"	15"	8"	4"
93-97	Ranger 4WD	6"	35"	12.5"	15"	8"	4"
93-97	Ranger 4WD	8"	36"	12.5"	15"	8"	4"
90-94	Explorer/Navajo 4WD	2"	31"	12.5"	15"	8"	4"
90-94	Explorer/Navajo 4WD	4"	32"	12.5"	15"	8"	4"
90-94	Explorer/Navajo 4WD	6"	33"	12.5"	15"	8"	4"
83-92	Ranger Bronco II 4WD	2"	28"	12.5"	15"	8"	4"
83-92	Ranger Bronco II 4WD	4"	30"	12.5"	15"	8"	4"
83-92	Ranger Bronco II 4WD	6"	32"	12.5"	15"	8"	4"
83-92	Ranger Bronco II 4WD	8"	34"	12.5"	15"	8"	4"
<b>Ford F150/Bronco</b>							
03	Expedition	2"	32"	11.5"	16"	8"	3.625"
97-02	F150	6"	35"	12.5"	16"	8"	4.5"
92-96	F150, Bronco	2"	32"	12.5"	15"	10"	4"
92-96	F150, Bronco	4"	33"	12.5"	15"	10"	4"
92-96	F150, Bronco	6"	35"	12.5"	15"	10"	4"
92-96	F150, Bronco	8"	37"	12.5"	15"	10"	4"
87-91	F150, Bronco	2"	34"	12.5"	15"	10"	4"
87-91	F150, Bronco	4"	36"	12.5"	15"	10"	4"
87-91	F150, Bronco	6"	38"	12.5"	15"	10"	4"
87-91	F150, Bronco	8"	39"	12.5"	15"	10"	4"
80-86	F150, Bronco	2"	33"	12.5"	15"	10"	4"
80-86	F150, Bronco	4"	35"	12.5"	15"	10"	4"
80-86	F150, Bronco	6"	37"	12.5"	15"	10"	4"
80-86	F150, Bronco	8"	38.5"	12.5"	15"	10"	4"
69-79	F150, 78-79 Bronco 4WD	2"	33"	12.5"	15"	10"	4"
69-79	F150, 78-79 Bronco 4WD	4"	35"	12.5"	15"	10"	4"
69-79	F150, 78-79 Bronco 4WD	6"	37"	12.5"	15"	10"	4"
69-79	F150, 78-79 Bronco 4WD	9"	40"	12.5"	15"	10"	4"
66-77	Bronco w/ cut-outs	3"	33"	12.5"	15"	10"	4"
66-77	Bronco w/ cut-outs	5"	35"	12.5"	15"	10"	4"
66-77	Bronco w/ cut-outs	7"	37"	12.5"	15"	10"	4"

Year	Vehicle Model	Max Tire Lift	Max Tire Height	Max Tire Width	Wheel Diameter	Wheel Width	Wheel Offset
<b>Ford F-250 F-350</b>							
99-03	F-250/F-350 SuperDuty 4WD	2"	33"	12.5"	16.5"	9.75"	4.625"
99-03	F-250/F-350 SuperDuty 4WD	4"	35"	12.5"	16.5"	9.75"	4.625"
99-03	F-250/F-350 SuperDuty 4WD	6"	36"	12.5"	16.5"	9.75"	4.625"
99-03	F-250/F-350 SuperDuty 4WD	8"	38"	12.5"	16.5"	9.75"	4.625"
92-98	F-350 Monobeam 4WD	2"	34"	12.5"	16.5"	9.75"	4.625"
92-98	F-350 Monobeam 4WD	4"	36"	12.5"	16.5"	9.75"	4.625"
92-98	F-350 Monobeam 4WD	6"	38"	12.5"	16.5"	9.75"	4.625"
86-91	F-350 Monobeam 4WD	2"	36"	12.5"	16.5"	9.75"	4.625"
86-91	F-350 Monobeam 4WD	4"	38"	12.5"	16.5"	9.75"	4.625"
86-91	F-350 Monobeam 4WD	6"	40"	12.5"	16.5"	9.75"	4.625"
92-98	F-250 Twin I Beam 4WD	2"	33"	12.5"	16.5"	9.75"	4.625"
92-98	F-250 Twin I Beam 4WD	4"	35"	12.5"	16.5"	9.75"	4.625"
92-98	F-250 Twin I Beam 4WD	6"	37"	12.5"	16.5"	9.75"	4.625"
80-91	F-250, F-350 Twin I Beam 4WD	2"	33"	12.5"	16.5"	9.75"	4.625"
80-91	F-250, F-350 Twin I Beam 4WD	4"	35"	12.5"	16.5"	9.75"	4.625"
80-91	F-250, F-350 Twin I Beam 4WD	6"	37"	12.5"	16.5"	9.75"	4.625"
92-96	F-250, F-350 2WD	2"	32"	12.5"	16"	8"	3.75"
92-96	F-250, F-350 2WD	4"	34"	12.5"	16"	8"	3.75"
92-96	F-250, F-350 2WD	6"	36"	12.5"	16"	8"	3.75"
77.5-79	F-250 Low Boy 4WD	2"	35"	12.5"	16.5"	9.75"	3.75"
77.5-79	F-250 Low Boy 4WD	4"	37"	12.5"	16.5"	9.75"	3.75"
77.5-79	F-250 Low Boy 4WD	6"	40"	12.5"	16.5"	9.75"	3.75"
66-77	F-250 Highboy	2"	38"	12.5"	16.5"	9.75"	3.75"
66-77	F-250 Highboy	4"	40"	12.5"	16.5"	9.75"	3.75"
<b>Jeep</b>							
97-03	Wrangler TJ	2"	32"	11.5"	15"	8"	3.75"
97-03	Wrangler TJ	4"	34"	12.5"	15"	8"	3.75"
97-03	Wrangler TJ	6"	35"	12.5"	15"	10"	3.75"
97-03	Wrangler TJ	8"	37"	12.5"	15"	10"	3.75"
97-03	Wrangler TJ	10"	38"	12.5"	15"	10"	3.75"
87-96	Wrangler YJ	2"	31"	10.5"	15"	8"	3.75"
87-96	Wrangler YJ	4"	33"	12.5"	15"	8"	3.75"
87-96	Wrangler YJ	6"	35"	12.5"	15"	8"	3.75"
55-86	CJ and Scrambler	2"	31"	12.5"	15"	8"	3.75"
55-86	CJ and Scrambler	4"	33"	12.5"	15"	10"	3.75"
99-01	Grand Cherokee WJ	3"	31"	10.5"	16"	8"	3.75"
93-98	Grand Cherokee ZJ	3"	31"	10.5"	15"	8"	3.75"
3-Feb	Liberty	2.5"	31"	10.5"	16"	8"	5"
84-99	Cherokee XJ Midsize	2"	30"	9.5"	15"	7"	3.75"
84-99	Cherokee XJ Midsize	3"	31"	10.5"	15"	8"	3.75"
86-92	Comanche Midsize	3"	31"	10.5"	15"	8"	3.75"
74-91	J10, J20, Cher, Wagoneer	4"	35"	12.5"	15"	10"	3.75"
<b>Toyota</b>							
96-01	4 Runner	2.5"	32"	11.50"	15"	8"	3.5"
3-Jan	Sequoia	2.5"	32"	11.50"	16"	8"	3.5"
00-01	Tundra	2.5"	32"	11.50"	16"	8"	3.5"
96-03	Tacoma	3"	31"	10.5"	15"	8"	3.5"
86-95	IFS Pickup 4WD	4"	33"	12.5"	15"	8"	3.75"
84-85	Pickup, 4 Runner 4WD	3"	33"	12.5"	15"	8"	3.75"
84-85	Pickup, 4 Runner 4WD	5"	35"	12.5"	15"	8"	3.75"
84-85	Pickup, 4 Runner 4WD	7"	37"	12.5"	15"	8"	3.75"
79-83	Pickup, 4 Runner 4WD	3"	35"	12.5"	15"	8"	3.75"
79-83	Pickup, 4 Runner 4WD	5"	37"	12.5"	15"	8"	3.75"
79-83	Pickup, 4 Runner 4WD	7"	39"	12.5"	15"	8"	3.75"
64-80	Landcruiser 4WD	2"	32"	12.5"	15"	8"	3.75"
64-80	Landcruiser 4WD	4"	35"	12.5"	15"	8"	3.75"
72-81	Scout II 4WD	2"	31"	12.5"	15"	8"	3.75"
72-81	Scout II 4WD	4"	33"	12.5"	15"	8"	3.75"

**FOOT NOTE:**  
THIS GUIDE IS TO BE USED STRICTLY AS A REFERENCE.